



SET UP INSTRUCTIONS:

- Step 1:** Locate base axle in box and push/ insert the fixings fully into the two poles at the bottom of the beach cart frame. Use Allen Key tool provided and tighten fasteners.
Note: It is recommended that the base axle remains permanently fixed to the cart.
- Step 2:** Lift/fold the cart handle upwards, pull out spring loaded securing clips, and lock the cart handle into position.
- Step 3:** Remove wheel securing clips, slide on wheels and return the spring-loaded securing clips through holes to secure wheels. (Wheels can also be removed for storage of cart in car/garage/shed).
Note: Ensure spring loaded clips are secured with positive spring tension to retain clip on axle pole ensuring they cannot fall off axle.
- Step 4:** Pull out stability/standing leg at bottom of cart and lock into plastic fitting.
- Step 5:** Secure items onto Beach Cart by using expandable cargo net provided. The cargo net can be placed and secured over the plastic fittings found around the cart at top handlebar, middle spring-loaded clips and bottom securing clips.

MAINTENANCE INSTRUCTIONS:

- Tip 1:** The Beach Carts have moving parts and must be maintained and checked regularly before use.
- Tip 2:** Always check all fasteners, bolts and nuts are secured before and after use. These fasteners may loosen after multiple folding – unfolding sequences.
- Tip 3:** Rinse and wash beach carts regularly to clean and remove built up of sand or debris.
- Tip 4:** Interchangeable wheels can be removed for cleaning and to allow the carts to be folded and stored more compactly.

WARNINGS:

- # 1:** The Beach Carts are designed to carry equipment up to 90Kgs/ 198lbs. DO NOT EXCEED WEIGHT LIMITS.
- # 2:** Children must be supervised at all times when using the beach cart.
- # 3:** Beach Carts are designed to carry equipment/items only. DO NOT TRANSPORT CHILDREN ON THE CART.
- # 4:** Avoid carrying/ packing sharp objects in the beach carts to prevent damaging the cart materials.
- # 5:** Only use beach carts for their intended purposes. Any deliberate mis-use may void any warranties.
- # 6:** Ensure balloon wheels are inflated to the recommended pressures in the maintenance instructions. Over-inflation of beach wheels will cause them to oversize and rub on fittings. If this occurs, please deflate the wheel to the recommended manufacturer pressures.